

Single Orifice Air Valve

Pressure Rating: PN 10
 Material of Construction: Ductile Cast Iron GGG 40/50



DN 50- DN 300

Catalogue No: 8-2210010

Range of application: Potable water				
Size DN	Pressure rating PN	Hydrotest pressure in bar		Admissible working pressure in bar up to 70°C
		Body	Seat	
50 - 300	10	15	10	10


In case of order please specify the working conditions



Materials / Equipment	
Catalogue No.	8-2210010
Body	GGG 40/50
Covers	GGG 40/50
Ball	Stainless steel 1.4301
Gaskets	EPDM or NBR
Bolts and nuts	Stainless steel A2
Corrosion protection	Epoxy powder coated RAL 5015

size DN mm	Dimensions			Weight kg	Volume m³
	D mm	L mm	H mm		
50	165	180	260	14	0.01
80	200	230	294	20	0.02
100	220	280	353	35	0.02
150	285	380	412	70	0.04
200	340	450	580	120	0.09
250	395	450	580	132	0.11
300	445	450	580	144	0.01

We reserve the right to make technical modifications



SAUDI VALVES MANUFACTURING

Tel.: +966 3 341 8514 - Fax: +966 3 341 8515
 P. O. Box 10137 Jubail Industrial City, 31961 The Kingdom of Saudi Arabia
 E-mail: info@saudivalves.com - Internet: www.saudivalves.com



20.03.2009