

Air Valve for Raw Sewage

Pressure Rating: PN 10
Material of Construction: Ductile Cast Iron GGG 40/50



DN 50 - DN 300

Catalogue No: 8-2310010

Range of application: Raw Sewage				
Size DN	Pressure rating PN	Hydrotest pressure in bar		Admissible working pressure in bar up to 70°C
		Body	Seat	
50 - 300	10	15	11	10

In case of order please specify the working conditions



Materials / Equipment	
Catalogue No.	8-2310010
Body	GGG 40/50
Covers	GGG 40/50
Float	Stainless steel 1.4571
Gaskets	NBR
Bolts and nuts	Stainless steel A4
Corrosion protection	Epoxy powder coated RAL 5015

size DN mm	Dimensions			Weight kg	Volume m ³
	D1 mm	D mm	H mm		
50	165	261	680	32	0.40
80	200	261	680	32	0.40
100	220	261	680	34	0.40
150	285	261	680	37	0.04
200	340	446	680	128	0.09
250	405	446	680	136	0.11
300	460	446	680	149	0.12

We reserve the right to make technical modifications



SAUDI VALVES MANUFACTURING

Tel.: +966 3 341 8514 - Fax: +966 3 341 8515

P. O. Box 10137 Jubail Industrial City, 31961 The Kingdom of Saudi Arabia

E-mail: info@saudivalves.com - Internet: www.saudivalves.com

ISO 9001

BUREAU VERITAS
Certification



N° 215125

20.03.2009